



BSI 75-B Slicer

1370 West Main St.
Salem, IL 62881
Phone: 618-548-3555
Fax: 618-548-3557
Email: sales@bettendorfstanford.com
Web: www.Bettendorfstanford.com

BSI 75-B Slicer Features

Standard Features:

- Stainless steel frame features paint free construction and easy access guarding
- Aluminum guards and doors for lightweight handling ease
- Slice thickness adjusting mechanism easily removed for wash-down cleaning
- Blade guides are offset to eliminate build-up
- Single point infeed and outfeed rail adjustments
- Interlock limits on all doors meet Category 3 safety standards
- Automatic broken blade shut-off
- Pneumatic double loaf eliminator clutch on outfeed
- Last loaf ejector
- Drum scrapers
- Choice of frame handing (Right or Left Hand blade input and controls)
- Hook-up to any standard packaging machine

Options:

- Automatic blade honing with timer and ceramic stones
- Blade oiling system, eliminates heat and gluten buildup
- Special slice thickness ranges from 1/4" to 5/8" (6.4mm to 15.9mm) or 3/8" to 1" (9.5mm to 25.44mm)
- Heel remover
- Dual controls from right and left sides

Specifications:

- Slicing speed up to 90 loaves per minute
- Minimum loaf size: 6"L x 2"H x 3"W (152mm x 51mm x 76mm)
- Maximum loaf size: 16"L x 6"H x 10"W (432mm x 152mm x 254mm)
- Electrical 230/380/460 Volt, 50/60 Hz., 3 Ph., 5 HP