



Automatically dispense an even coverage of product over a pan, conveyor, or dough line. Works great with any product with a 10% or less moisture content. Flour, starch, oats, seeds, sugar, salt, cinnamon/sugar, etc.

Portable and easy to clean!

Completely enclosed system to **reduce waste.**



Topping Applicator

1370 West Main St.
Salem, IL 62881
Phone: 618-548-3555
Email: sales@bettendorfstanford.com
Web: www.BettendorfStanford.com

1370 West Main St.
Salem, IL 62881
Phone: 618-548-3555
Email: sales@bettendorfstanford.com
Web: www.BettendorfStanford.com

Topping Applicator Features



Operational Features:

- 10 to 48 inch slotted tubes with 2mm, 3mm, 4mm, and 5mm slot sizes
- Automatic return of topping through undispensed tube
- Product eye for product detection
- AB PLC and HMI for timer control and adjustment
- Quick clean release slides on bottom of main hopper and return hopper for easy sanitation
- Helicoid 1/4 round or flat stock
- Powder coated stand with fixed height (adjustable +/- 4 inches)

Topping Applicator Features



Standard Features:

- Control Techniques servo
- Stainless steel construction
- Variable speed 3ph (customer specified voltage)

Safety Features:

- NEMA 4 enclosure
- DC control voltage
- Fastened guards and covers